


ATIS ★ 128.125		[USA] SL-2904 (AU)				Rwy	Knots	60	120	180	240
LINZ TOWER ★						27 (A)	V/V(fpm)	400	800	1200	1600
118.8						27 (B)	V/V(fpm)	205	410	615	820
LINZ RADAR (APP)						Minimum ATC Climb Rate					
119.75						(A) To 2000					
						(B) 2000 to 8000					



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 27: Track 266° to 3000, thence..

Initial clearance limit FL60:

ADLET 1L: Turn right and intercept LINZ R-020 inbound to ADLET. Cross LINZ 10 DME at or above 5000, cross LINZ 14 DME at or above 6000.

Initial clearance limit FL80:

GRZ 2L: Turn left and intercept LINZ R-143 inbound to GRZ VOR/DME. Cross LINZ 11 DME at or above 5000. Cross LINZ 24 DME at or above 8000. Cross LINZ 35 DME at or above FL110.

GRZ 2L: COMMUNICATION FAILURE PROCEDURE: Squawk 7600 and maintain FL80 until LINZ 20 DME, then climb to FL110. Maintain FL110 for 3 min, then climb to the filed flight plan cruising level.

Initial clearance limit FL60:

STO 1L: Turn right and intercept the LINZ R-079 inbound to the STO VOR/DME. Cross LINZ 23 DME at or above 6000.