


# RADAR INSTRUMENT APPROACH MINIMUMS

## WIESBADEN AAF (ETOU)

RADMINs

**WIESBADEN AAF (ETOU)**, GERMANY (06075 USA)

**ELEV 461**

**RADAR - (E)** 140.95 123.3 278.925 344.0 

|     | <u>RWY</u> | <u>GS/TCH/RPI</u> | <u>CAT</u> | <u>DH/</u><br><u>MDA-VIS</u> | <u>HAT/</u><br><u>HAA</u> | <u>CEIL-VIS</u> |
|-----|------------|-------------------|------------|------------------------------|---------------------------|-----------------|
| PAR | 25         | 3.0°/50/969       | ABCD       | <b>711</b> -1600m            | 250                       | (300-1600m)     |
|     | 07         | 3.0°/50/910       | ABCD       | <b>706</b> -1600m            | 250                       | (300-1600m)     |
| ASR | 25 ①       |                   | AB         | <b>920</b> -1600m            | 459                       | (500-1600m)     |
|     |            |                   | C          | <b>920</b> -2000m            | 459                       | (500-2000m)     |
|     |            |                   | D          | <b>920</b> -2400m            | 459                       | (500-2400m)     |
|     | 07         |                   | AB         | <b>1060</b> -1600m           | 604                       | (600-1600m)     |
|     |            |                   | C          | <b>1060</b> -2800m           | 604                       | (600-2800m)     |
|     |            |                   | D          | <b>1060</b> -3200m           | 604                       | (600-3200m)     |
| CIR | 07/25      |                   | A          | <b>1060</b> -1600m           | 599                       | (600-1600m)     |
|     |            |                   | B          | <b>1120</b> -1600m           | 659                       | (700-1600m)     |
|     |            |                   | C          | <b>1120</b> -2800m           | 659                       | (700-2800m)     |
|     |            |                   | D          | <b>1120</b> -3200m           | 659                       | (700-3200m)     |

\*CAUTION: Missed Approach Minimum Climb Rate to 3000,

\*CAUTION: Do not cross TAU R-168 above 2500.

\*\*CAUTION: Missed Approach Minimum Climb Rate to 4000.

\*\*CAUTION: Do not exceed 4000 along FFM R-285.

|                  |          |     |     |     |      |
|------------------|----------|-----|-----|-----|------|
|                  | KNOTS    | 60  | 120 | 180 | 200  |
| *PAR/ASR Rwy 25  | V/V(FPM) | 300 | 600 | 900 | 1200 |
| **PAR/ASR Rwy 07 | V/V(FPM) | 217 | 434 | 651 | 868  |

MP 1200-1400Z++ Wed. Procedure not authorized when tower not in operation. ① 3 NM stepdown fix min alt 1420.

# RADAR INSTRUMENT APPROACH MINIMUMS