



NDB LJ 365	APCH CRS 137°	Rwy Idg TDZE 12,515 230 Arpt Elev 302	[USA] AL-2033 (GM)		KOLN/BONN (EDDK)	
* For inop ALS, increase vis CAT A,B to RVR 1520m, CAT C to RVR 1830m, CAT D to 2400m.				ALSF-1 	MISSED APPROACH: Climb straight ahead to 3000, when passing 2000 or 2.8 DME KBO, whichever is later, turn left to WYP VOR.	
ATIS 119.025 112.15	KOLN/BONN DIRECTOR 121.05 389.525	KOLN/BONN TOWER 124.975 253.025	GND CON 121.725	CLNC DEL 121.85	MIL GND SVC 136.25 312.1	LANGEN RADAR 126.325 312.425



DME REQUIRED



LEGDU KBO 9.8		TA 5000	2000 KBO 2.8	3000 WYP
137° 3000		KBO 5	LJ NDB	1480
10 NM		3.00° TCH 54	KBO 1.8	VOR/DME
4.8 NM		3.2 NM	7	
CATEGORY	A	B	C	D
S-14L*	700/730m 470(400-730m)	700/1220m 470 (400-1200m)	700/1520m 470 (400-1600m)	
CIRCLING	NOT AUTHORIZED			