


Rwy	Knots	60	120	180	240	300	360
* 32 Ⓐ	V/V(fpm)	390	780	1170	1560	1950	2340
† 32 Ⓑ	V/V(fpm)	400	800	1200	1600	2000	2400
† 32 Ⓒ	V/V(fpm)	360	720	1080	1440	1800	2160

\* Minimum † ATC Climb Rate

- Ⓐ KOVAS 6A,  
CARBONARA 6A  
to 400  
KOVAS 6C,  
CARBONARA 6C  
to 3600
- Ⓑ KOVAS 6A 400 to FL150
- Ⓒ KOVAS 6C 3600 to FL150



EMERG SAFE ALT 100 NM 8400

TA 6000

## DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 32:

After take-off proceed on track bearing 318° (318° CAG Locator) until leaving 1000 ft, then turn right on track 181° to intercept and follow heading 138° CAG Locator inbound to CAG Locator. Thence...

ATC Discretion:

After take-off proceed on track 318° until leaving 1000 ft, then turn left to follow heading 103° CAG Locator inbound CAG Locator.

## KOVAS 6A:

Proceed on bearing 138° CAG Locator till DEC TACAN 14 DME, then turn left to intercept and follow heading 299° DEC NDB. When at DEC TACAN 3 DME turn right to intercept and follow bearing 015° DEC NDB inbound to KOVAS. Max turning speed 220 KIAS.

(Continued on next page)