

ADANA, TURKEY

HI/LO TACAN or ILS RWY 05

LOC I-DAN	APCH CRS	Rwy Idg
109.3	049°	TDZE 194
		Arpt Elev 238

JAL-2691 [USAF]

INCIRLIK AB (LTAG)

- * When ALS inop, increase vis to 1200m.
 ** When ALS inop, increase vis CAT ABCD to 1600m, CAT E to 2000m.
 *** When ALS inop, increase vis CAT ABC to 1600m, CAT DE to 2000m.






MISSED APPROACH: Climb straight ahead on DAN R-050 to CHRLE and hold. Maintain 5000.

ATIS	INCIRLIK APP CON	INCIRLIK TOWER	GND CON	PAR
314.175	128.0 296.75	129.4 264.775	123.025 313.6	

**** Circling not authorized North of Rwy 05-23.

7953

RADAR or DME REQUIRED FOR LOCALIZER ONLY APPROACH



CATEGORY	A	B	C	D	E
S-ILS 05 *	394-800m 200 (200-800m)				
S-LOC 05 **	520-800m 326 (300-800m)	520-1200m 326 (300-1200m)			
S-TAC 05 ***	560-800m 366 (400-800m)	560-1200m 366 (400-1200m)			
CIRCLING ****	680-1600m 442 (500-1600m)	700-1600m 462 (500-1600m)	700-2400m 462 (500-2400m)	800-3200m 562 (600-3200m)	1080-4800m 842 (900-4800m)
S-PAR 05 *	394-800m 200 (200-800m) GS 2.50°				

ADANA, TURKEY

37°00'N-35°26'E

INCIRLIK AB (LTAG)

Orig 06187

HI/LO TACAN or ILS RWY 05

Effective 3 AUG 2006 - 31 AUG 2006