

04330

BELLE FIVE DEPARTURE TRUE

SHL-1958 [USAF]

THULE AB (BGTI)


THULE, GREENLAND

GND CON
119.9 275.8
THULE TOWER ★
126.2 255.6
THULE APP CON
134.1 363.8
CLNC DEL
119.9

Rwy	Knots	60	120	180	240
8T	V/V(fpm)	370	740	1110	1450

Minimum Climb Rate to 4000

**RADAR or DME
Required**
**SPECIAL AIRCREW AND AIRCRAFT
AUTHORIZATION REQUIRED**




CAUTION: High terrain
in all quadrants.

Severe turbulence may occur near ice cap
in area True N-S. Expect severe down drafts
on final approach when wind speeds exceed
30 kts from 125T-225T.

Do not exceed 250 KIAS
until leaving 6000.

Procedure design based on true
course and radials. Magnetic
variation not applied.



EMERG SAFE ALT 100 NM 15,600

① 4.6 NM from Rwy 8T

Tlv FL90
TA 6500

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 08T: Depart on track 100°T (169°G) until leaving 700, then turn right and proceed direct to THT R-264T/13 DME then proceed outbound on THT R-264T. Leaving 6000 MSL terminate prescribed departure track and proceed as directed in ATC clearance.

TAKE-OFF RWY 26T: Depart on track 264°T (333°G). Proceed via THT R-264T until reaching 6000 then as directed in ATC clearance.

BELLE FIVE DEPARTURE TRUE

THULE, GREENLAND
THULE AB (BGTI)

Effective 3 AUG 2006 - 31 AUG 2006