



TACAN RMS Chan 81	APCH CRS 080°	Rwy Idg 10,498 THRE 761 Arpt Elev 776	AL-2231 [USAF]		RAMSTEIN AB (ETAR)		
* When ALS inop, increase CAT B vis to 2000m, CAT C vis to 3600m, CAT D vis to 4000m and CAT E vis to 4400m. ** Circling not authorized S of Rwy 08-26.			ALSF-1 	MISSED APPROACH: Climbing to 5000 intercept the RMS R-086 to FRANK and hold.			
ATIS★ 124.275 284.325		LANGEN RADAR 129.675 256.675		RAMSTEIN TOWER 133.2 386.75		GND CON 121.775 308.775	PAR



EMERG SAFE ALT 100 NM 7200					ELEV 776
					FRANK RMS 17
CATEGORY	A	B	C	D	E
S-08 *	1520/1600m 759 (800-1600m)	1520-2800m 759 (800-2800m)	1520-3200m 759 (800-3200m)	1520-3600m 759 (800-3600m)	1520-3600m 759 (800-3600m)
CIRCLING **	1660-1600m 878 (900-1600m)	1680-2000m 898 (900-2000m)	2020-4800m 1238 (1300-4800m)	2260-4800m 1478 (1500-4800m)	2620-4800m 1838 (1900-4800m)
S-PAR 08	964/1220m	200 (200-1200m)	GS 3.00°		

Effective 3 AUG 2006 - 31 AUG 2006