

LOC HN
108.9

APCH CRS
260°

Rwy Idg
TDZE
Arpt Elev
8005
38
39

[USAF] AL-3371 (GAF)

HOHN (ETNH)

▼

* When ALS inop, increase vis to 1200m.
** When ALS inop, increase CAT AB vis to 1600m,
CAT CD vis to 2000m.

ⓑⓃ

MISSED APPROACH: Turn left climbing to 2000
and rehome HN NDB.

| | | |
|----------------------------------|----------------------------------|---------|
| HOHN RADAR 141.1 375.5 | HOHN TOWER 141.7 369.3 | ASR/PAR |
|----------------------------------|----------------------------------|---------|

***When ALS inop, increase CAT AB vis to 1600m,
CAT C vis to 2000m, CAT D vis to 2400m.
† When ALS inop, increase CAT AB vis to 1600m,
CAT CD vis to 2000m.

NDB REQUIRED

LOCALIZER 108.9
HN

MM OM

IAF
HOHN
344 HN

080° 260° 110° 380°

10 NM

820

MSA HN 2.5 NM
2000

2000 HN

NDB/OM TA 5000

4000 110° 260° 2000

MM 1200

GS 3.00° TCH 58

0.5 NM 3.5 NM

Remain within 10 NM

ELEV 39

164 A

HIRL Rwy 08-26

LOC FAF to MAP 3.5 NM

| | | | | | |
|---------|------|------|------|------|------|
| Knots | 60 | 90 | 120 | 150 | 180 |
| Min:Sec | 3:30 | 2:20 | 1:45 | 1:24 | 1:10 |

NDB FAF to MAP 4.0 NM

| | | | | | |
|---------|------|------|------|------|------|
| Knots | 60 | 90 | 120 | 150 | 180 |
| Min:Sec | 4:00 | 2:40 | 2:00 | 1:36 | 1:20 |

HOHN, GERMANY
Orig 06019

54°19'N-09°32'E

HOHN (ETNH)

NDB/ILS RWY 26

Effective 3 AUG 2006 - 31 AUG 2006