


LOC I-DSE 111.5	APCH CRS 053°	Rwy ldg THRE 8858 Arpt Elev 121 147	[USAF] AL-3012 (GM)		DUSSELDORF (EDDL)
* When ALS inop, increase RVR to 1220m, vis to 1200m. ** When ALS inop, increase CAT AB RVR to 1520m, vis to 1600m; CAT C RVR to 1830m, vis to 2000m; CAT D RVR to 2400m, vis to 2400m.			ALSF-1 	MISSED APPROACH: Climb on track 053° to DUS 3 DME. Turn left on track 268° inbound to LMA climbing to 4000.	
ATIS ★ 123.775	LANGEN RADAR 133.775 275.8	DUSSELDORF TOWER 118.3 378.35	GND CON 121.9	CLNC DEL 121.775	

DME and NDB REQUIRED

CAUTION: Short intmed segment, recommend early configuration.



NATOS 8.9	4000	DUS 3	ELEV 147
tr 056°			Rwy 05L-23R ldg 7874' Rwy 05R-23L ldg 8858'
OM 4.1			
MM 1.6			
GS 3.00° TCH 51			
1.9 NM	2.9 NM	3.5 NM	
CATEGORY	A	B	C
S-ILS 05R *	321/730m 200 (200-800m)		
S-LOC 05R **	600/730m 479 (500-800m)	600/1220m 479 (500-1200m)	600/1520m 479 (500-1600m)
CIRCLING	NOT AUTHORIZED		