

TACAN RMS
Chan 81

APCH CRS
261°

Rwy Idg
8647
TDZE
782
Arpt Elev
782

AL-2231 [USAF]

RAMSTEIN AB (ETAR)


✦

* When ALS inop, increase CAT A vis to 2000m, CAT C vis to 3600m, CAT D vis to 4000m, CAT E vis to 4400m.
** Circling not authorized S of Rwy 09-27.

BP

MISSED APPROACH: Climbing to 5000 tr 261° to RMS 2 DME, turn right to intcp RMS R-270 to 12 DME then turn right intcp RMS R-272 outbound direct MAPIG and hold.

ATIS★ 124.275 284.325	LANGEN RADAR 129.675 256.675	RAMSTEIN TOWER 133.2 386.75	GND CON 121.775 308.775	PAR
--------------------------	---------------------------------	--------------------------------	----------------------------	-----



5000
tr
261°

RMS 2

RMS R-270

TA 5000

FRANK R-086 17

ELEV 782

TWR 930

THRE 776

261° to TACAN

1287 A

TDZL/CL Rwy 26

REIL Rwy 08-26

HIRL Rwy 08-26

1.5

6

11

261°

290°

5000

4000

2700

3.52°

TCH 49

VGSI and descent angle not coincidental.

CATEGORY	A	B	C	D	E
S-27 *	1540/800m 758 (800-800m)	1540-1200m 758 (800-1200m)	1540-2800m 758 (800-2800m)	1540-3200m 758 (800-3200m)	1540-3600m 758 (800-3600m)
CIRCLING **	1690-2000m 908 (1000-2000m)	1710-2000m 928 (1000-2000m)	2020-4800m 1238 (1300-4800m)	2260-4800m 1478 (1500-4800m)	2620-4800m 1838 (1900-4800m)
S-PAR 27 ***	1032/730m	250 (300-800m)	GS 3.00°		