


# RADAR INSTRUMENT APPROACH MINIMUMS

## AMENDOLA (LIBA)

RADMINs

**AMENDOLA (LIBA)**, ITALY (06075 USAF)

**ELEV 183**

**RADAR** - Call GCA (E) 123.3 279.125 344.0 315.75 385.4 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR	11	2.6°/34/-	ABCDE	<b>401</b> -1600m	221	(300-1600m)
	29 ①	2.6°/33/-	ABCDE	<b>407</b> -1200m	222	(300-1200m)

GCA hrs 0715-1515Z++ Mon-Thu, 0715-1045Z++ Fri; OT base necessity only. MP 1200Z-SS+30 Sat in VMC only. ① When ALS inop, increase vis CAT AB to 1400m; CAT CD to 1600m.

### MISSED APPROACH

RWY 11: Proceed on 113°, climbing to 5000; pass AME NDB at or above 3000, turn left to reach AME NDB at 5000.

RWY 29: Proceed on 295°, climbing to 5000; crossing 3500, turn left to reach AME NDB at 5000.

# RADAR INSTRUMENT APPROACH MINIMUMS