

TACAN NSY
Chan 49

APCH CRS
272°

Rwy ldg 7728
TDZE 72
Arpt Elev 79


[USN] AL-2701 (ITAF)

SIGONELLA (LICZ)

▼ * When ALS inop, increase vis CAT AB to 1600m, CAT CD to 2000m, CAT E to 2400m.
** Circling not authorized N of Rwy 10-28.

⬆ MISSED APPROACH TYPE (A): Climb on rwy heading to 1000 within 2 NM after NSY, turn left, climb to 4000 heading 059° to join and fly R-092 to 14 DME (GOLFO) and hold.

ATIS 138.175 387.625	CATANIA APP CON 119.25 340.1	SIGONELLA TOWER 118.05 337.6	GND CON 121.95 279.175	ASR/PAR
-------------------------	---------------------------------	---------------------------------	---------------------------	---------



1000 4000
↑
hdg 059°

TA 7000
GOLFO R-092 14
4000

TACAN
1 4 6
1000 1500
5 NM

CATEGORY	A	B	C	D	E
S-28L *	480-1200m 408 (500-1200m)				480-1600m 408 (500-1600m)
CIRCLING **	560-1600m 479 (500-1600m)	560-2400m 479 (500-2400m)	640-3200m 559 (600-3200m)	1040-4800m 959 (1000-4800m)	
S-PAR 28L ***	322-1200m 250 (300-1200m)		GS 2.5 °		
S-PAR 28L ***	322-1200m 250 (300-1200m)		GS 3.0 °		

ELEV 79

187
Λ

208
Λ

147
Λ

217 165
Λ Λ

101 10R
Λ

8077 × 1.48
Λ

8012 × 2
Λ

28R
Λ

28L
Λ

TDZE 72

272° to TACAN

Rwy 10R ldg 7734'
Rwy 28L ldg 7728'
HIRL Rwy 10R-28L
MIRL Rwy 10L-28R
REIL all Rwy