


RADAR INSTRUMENT APPROACH MINIMUMS

GRAZZANISE (LIRM)

RADMINs

GRAZZANISE (LIRM), ITALY (USAF 06075 ITAF)

ELEV 29

RADAR - GCA (E) 123.3 279.1 344.0 278.375 385.4 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR	06 ①	2.6°/49/1070	AB	278 -800m	260	(300-800m)
			CDE	278 -1200m	260	(300-1200m)

① Opr 0700-1430Z++ Mon-Thu; 0700-1030++ Fri with 30 min PN; Sat, hol for Base necessities only. MP fst Wed mthly in VMC only. When ALS inop, increase vis to 1600m.

MISSED APPROACH: If not otherwise instructed by GCA controller, continue on track 060° climbing to 3000.

Cross 900 (within 2 DME GRA TAC), turn left on track 196° to intercept GRA R-243 inbound to holding on GRA R-243/12 DME at 3000. Hold between 12 and 17 DME inbound track 063°, left turns. Max holding first left turn 250 KIAS. Holding procedure Max holding 265 KIAS.

RADAR INSTRUMENT APPROACH MINIMUMS