


TACAN Chan <b>49</b>	APCH CRS <b>102°</b>	Rwy ldg TDZE Arpt Elev <b>7734</b> <b>79</b>	[USN] AL-2701 (ITAF)	SIGONELLA (LICZ)
* When ALS inop, increase vis CAT AB to 1600m, CAT C to 2000m, CAT D to 2400m, CAT E to 2800m. ** Circling not authorized N of Rwy 10-28.			(X)	MISSED APPROACH: Climb to 4000 on NSY R-092 to NSY R-092/14 DME (GOLFO) and hold.

ATIS <b>138.175 387.625</b>	CATANIA APP CON <b>119.25 340.1</b>	SIGONELLA TOWER <b>118.05 337.6</b>	GND CON <b>121.95 279.175</b>	ASR/PAR
--------------------------------	--	--	----------------------------------	---------



NSY R-282

15

BASTA

12

TA 7000

9

7

3

0.6

4000

3500

2600

2000

700

NSY R-092

14

4000

NSY R-092

102°

102°

6.4 NM

CATEGORY

A

B

C

D

E

S-10R\*

560-1200m

479(500-1200m)

560-1600m

479

(500-1600m)

560-2000m

479

(500-2000m)

CIRCLING\*\*

560-1600m

479(500-1600m)

560-2400m

479

(500-2400m)

640-3200m

559

(600-3200m)

1040-4800m

959

(1000-4800m)

S-PAR 10R\*\*\*

331-1200m

250 (300-1200m)

GS 2.5°/3.0°

ELEV 79

187

102° to TACAN

208

147 TWR

8012222

8077148

217

165

28R

28L

TDZE 79

Rwy 10R Idg 7734'

Rwy 28L Idg 7728'

HIRL Rwy 10R-28L

MIRL Rwy 10L-28R

REIL all Rwy