


RADAR INSTRUMENT APPROACH MINIMUMS

TRAPANI/BIRGI (LICT)

RADMINs

TRAPANI/BIRGI (LICT), ITALY (USAF 06075 ItAF)

ELEV 25

RADAR ① - Call GCA (E) 123.3 122.8 344.0 279.1 369.475 385.4 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR	13 ②	2.5°/32/-	ABCDE	211-1200m	201	(300-1200m)
	31 ②	2.7°/32/-	ABCDE	225-1200m	201	(300-1200m)

① MP 0700-1400Z++ Fri in VMC only. ② When ALS inop, increase vis CAT CDE to 1600m.

MISSED APPROACH

RWY 13:

If not issued verbal missed approach instructions by the radar controller, climb to 3000 and track 128° direct TRP. At TRP turn right heading 346° and intercept TRP R-306 to 15 DME. Hold on the TRP R-306 inbound 15 to 20 DME, left turns. Max holding airspeed 265 KIAS.

RWY 31:

If not issued verbal missed approach instructions by radar controller, climb to 4000, turn left track 083° to intercept TRP R-126 outbound. Hold on the TRP R-126 inbound from 12 to 17 DME, left turns. Max holding airspeed 265 KIAS.

RADAR INSTRUMENT APPROACH MINIMUMS