ILS-T RWY 24

LOC INP	APCH CRS	Rwy ldg 7998 TDZE 223 Arpt Elev 294
109.5	236°	

[USN] AL-1686 (ITAF) CAPODICHINO (LIRN)

▼ * When ALS inop, increase vis 400m.
** Night circling to Rwy 06 not authorized.

*** MISSED APPROACH: As soon as possible climbing left turn to 6000 via hdg 180° (turn restricted to 180 KIAS) to join SOR VOR/DME R-342 to GEMMA, then direct SOR. Cross GEMMA at or above 3500, cross SOR at 6000.

ATIS	ROMA ACC	NAPOLI RADAR	NAPOLI TOWER	GND CON/CLNC DEL
135.975	127.35 314.5	124.35 234.05	118.5 257.8	121.9 235.15

***CAUTION: Missed Approach Minimum Climb Rate to 6000

Knots	60	120	180	240
V/V(fpm)	313	626	939	1252

ATC Minimum Climb Rate

IAF
POMIGLIANO
117.85 POM
Chan 125 (Y)
351

2546

CAUTION: Intmed seg descent grad varies fr 300 ft/NM to 367 ft/NM.

728

456

LOCALIZER 109.5
INP

OM

1745 640 610 948

200° 020°

R-200

4203

10 NM

R-342

GEMMA
SOR
8

SORRENTO
112.2 SOR
Chan 59

EMERG SAFE ALT 100 NM 12,000

POM 15 R-043 R-050 056°

043° Max 210 KIAS

050° Max 140 KIAS

236°

BENTO
POM 15

POM 12
POM 11
POM 9
POM 6

5220

MSA POM 2.5 NM
170°
5500
7500
010°

6000 hdg 180°

POM VOR/DME NDB OM

TA 8000

BENTO

6 9 11 12 15

6000 7000

1812

5000 5700

3900

GS 3.33°
TCH 51

4.3 NM

ELEV 294

236° 4.3 NM from VOR/DME NDB/OM

391 390 325 397 361 384

8422 x 148

0.9% UP

TDZE 223

TWR

Rwy 24 apch lighting 2018' non-standard.

Rwy 06 ldg 7313'
Rwy 24 ldg 7998'
HIRL Rwy 06-24
REIL Rwy 06-24

CATEGORY	A	B	C	D
S-ILS 24 *	670-2000m 447 (400-2000m)	680-2000m 457 (400-2000m)	690-2000m 467 (400-2000m)	700-2000m 477 (500-2000m)
S-LOC 24	NOT AUTHORIZED			
CIRCLING **	1200-2400m 906 (1000-2400m)		2160-4800m 1866 (1900-4800m)	

Effective 3 AUG 2006 - 31 AUG 2006