

RADAR INSTRUMENT APPROACH MINIMUMS

TWENTHE (EHTW)

RADMINs

TWENTHE (EHTW), NETHERLANDS (USAF 04134 RNLAf)

ELEV 114

RADAR - GCA: Director - (E) 118.575 122.1 344.475 Final 122.45 123.3 345.025 281.125



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	06	3.0°/41/775	ABCDE	200 -1200m	100	(100-1200m)
	24	3.0°/41/775	ABCDE	280 -1200m	166	(200-1200m)
ASR	24 ①		ABC	460 -1200m	346	(400-1200m)
			DE	460 -1600m	346	(400-1600m)
	06 ②		AB	560 -1200m	460	(500-1200m)
			C	560 -1600m	460	(500-1600m)
			DE	560 -2000m	460	(500-2000m)
CIR	ALL RWY		AB	760 -1600m	646	(700-1600m)
			C	760 -2800m	646	(700-2800m)
			DE	760 -3600m	646	(700-3600m)

Opr 0700-1545Z ++ Mon-Fri. ① When ALS inop, increase CAT ABC vis to 1600m, CAT DE vis to 2000m.

② When ALS inop, increase CAT AB vis to 1600m, CAT C vis to 2000m, CAT DE vis to 2400m.

RADAR INSTRUMENT APPROACH MINIMUMS