

LONDON, ENGLAND

ILS/DME RWY 05

LOC/DME I-SED 110.5 Chan 42	APCH CRS 045°	Rwy Idg 10,000 TDZE 331 Arpt Elev 348
---	-------------------------	--

[USN] AL-2234 (UK)

STANSTED (EGSS)

<p>▼ * When ALS inop, increase vis 400m. ** When ALS inop, increase vis CAT ABD 800m, CAT C 400m.</p>	<p>⓵</p>	<p>*** MISSED APPROACH: Climb straight ahead not above 3000. At I-SED 2 DME (BKY VOR/DME R-120) turn left to establish on BKY R-105. Cross BKY 5 DME at 3000. Continue to BKY at 3000 or as directed by ATC</p>
---	----------	---


ATIS 127.175 114.55	ESSEX RADAR 120.625	STANSTED TOWER 123.8	GND CON 121.725	CLNC DEL 121.95	ASR
-------------------------------	-------------------------------	--------------------------------	---------------------------	---------------------------	-----

Lowest holding level at LOREL/ASKEY is 7000 ft (flight level equivalent). However, when radar is out of service 6000 ft may be used as instructed by ATC.


Advise ATC if unable to receive BKY VOR/DME.

*** CAUTION: Missed Approach
Minimum Climb Rate to 3000

Knots	60	120	180	240
V/V(fpm)	300	600	900	1200



I-SED 6.6	TA 6000	3000	I-SED 2	BKY R-105	ELEV 348
-045°	2500 (2176)	1654			
GS 3.00° TCH 56					
	5.6 NM	1.0			
CATEGORY	A	B	C	D	
S-ILS 05 *	531-800m	200	(200-800m)		
S-LOC 05 **	680-800m 349 (400-800m)		680-1200m 349 (400-1200m)		
CIRCLING	920-1600m 572 (600-1600m)		1060-3200m 712 (800-3200m)	1060-3600m 712 (800-3600m)	
S-ASR 05	980-4000m	649	(700-4000m)		



LONDON, ENGLAND

51° 53' N-00° 14' E

STANSTED (EGSS)

05160

ILS/DME RWY 05

Effective 3 AUG 2006 - 31 AUG 2006