


RADAR INSTRUMENT APPROACH MINIMUMS

COTTESMORE (EGXJ)

RADMINs

COTTESMORE (EGXJ), ENGLAND (Amdt 3 USAF 06019 RAF)

ELEV 461

RADAR - Call TALKDOWN - (E) 123.3x 338.25 339.325 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ①	22 ②	3.0°/58/-	ABCDE	620 /800m	201	(200-800m)
	04	2.5°/42/-	AB	670 /1220m	209	(300-1200m)
	04	3.0°/51/-	CDE	670 /1520m	209	(300-1600m)

① MP 0800-1000Z++ 1st Wed. ② When ALS inop, increase vis CAT AB RVR to 1220m, vis to 1200m, CAT CDE RVR to 1520m, vis to 1600m.

LOST COMMUNICATION PROCEDURE (all runways): If unable to continue approach, carryout Missed Approach for runway in use and try to regain contact on any COTTESMORE frequency.

MISSED APPROACH PROCEDURE:

Rwy 04: Climb on track 045° to 2960 (2499), at 3 NM turn left to track 245°; call DIRECTOR.

Rwy 22: Climb on track 225° to 2920 (2501), at 3 NM turn left to track 065°; call DIRECTOR.

RADAR INSTRUMENT APPROACH MINIMUMS