


# RADAR INSTRUMENT APPROACH MINIMUMS

## VALLEY (EGOV)

RADMINS

**VALLEY (EGOV)**, WALES (USAF Amdt 2 06019 RAF)

**ELEV 37**

**RADAR** - ASR: DIRECTOR (E) 123.3x 125.225 396.85 344.0x PAR: TALKDOWN (E) 123.3x 313.55 385.4x 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ①	32	3.0°/60/-	AB	<b>230</b> -1200m	201	(200-1200m)
			CDE	<b>230</b> -1600m	201	(200-1600m)
	14 ②③	3.0°/53/-	ABCDE	<b>240</b> -1400m	207	(300-1400m)
	19 ④	3.0°/30/-	AB	<b>240</b> -1400m	204	(300-1400m)
			CDE	<b>240</b> -1600m	204	(300-1600m)

① PAR MP 0800-1200Z++ 1 st Wed. ② When ALS inop, increase CAT CDE vis to 1600m. ③ CAUTION: Do not cross 3 NM below 680 (640). ④ TCH does not meet standard of 32'.

LOST COMMUNICATIONS: Fly heading 360° climbing to 2533 (2500) Rwy 14, 2530 (2501) Rwy 32. Attempt contact on any VALLEY frequency.

MISSED APPROACH INSTRUCTIONS:

PAR Rwy 14: Climb on track 135° to 2540 (2500), call APPROACH.

PAR Rwy 19: Climb on track 191° to 2540 (2500), call APPROACH.

PAR Rwy 32: Climb on track 315° to 2530 (2500), call APPROACH.

# RADAR INSTRUMENT APPROACH MINIMUMS