

RADAR INSTRUMENT APPROACH MINIMUMS

CONINGSBY (EGXC)

RADMINs

CONINGSBY (EGXC), ENGLAND (USAF Amdt 1 06019 RAF)

ELEV 25

RADAR - ASR: Call DIRECTOR - (E) 277.5 344.0x PAR: Call TALKDOWN - (E) 123.3x 281.125 341.2



| | <u>RWY</u> | <u>GS/TCH/RPI</u> | <u>CAT</u> | <u>DH/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> |
|-----|------------|-------------------|------------|------------------------------|---------------------------|-----------------|
| PAR | 07 | 3.0°/39/- | AB | 230 -1400m | 208 | (300-1400m) |
| | | | CDE | 230 -1600m | 208 | (300-1600m) |
| | 25 ① | 3.0°/51/- | ABCDE | 230 -1400m | 205 | (300-1400m) |

ASR MP 0830-1030Z++ 2nd Fri. PAR MP 0830-1030Z++ 1st Mon. ① When ALS inop, increase CAT CDE vis to 1600m.

LOST COMMUNICATIONS PROCEDURE ALL RWY: If you lose radio contact and are unable to continue the approach, climb straight ahead to 2730 (2705), turn to track 070° and attempt contact on any published frequency.

MISSED APPROACH PAR RWY 07: Climb on track 075° to 2730 (2708), then left turn onto track 070°.

MISSED APPROACH PAR RWY 25: Climb on track 255° to 2730 (2705), then right turn onto track 070°.

RADAR INSTRUMENT APPROACH MINIMUMS