

RADAR INSTRUMENT APPROACH MINIMUMS

COLD LAKE (CYOD)

RADMINIS

COLD LAKE (CYOD), ALBERTA (USAF 06047 DND)

ELEV 1775

RADAR - (E) 119.4x 124.5x 128.2x 134.1x 248.4x 279.8x 269.6x 294.6x 324.3x 336.0x
350.5x 378.5x 398 ①

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ②	13L	3.0°/44/850	ABCDE	1972 -½	200	(200-½)
	22	3.0°/44/850	ABCDE	1967 -¾	200	(200-¾)
	31R	3.0°/44/850 ③	ABCDE	1975/26	200	(200-½)

① Used in event of acft com failure. ② MP Tue 0100-0700Z+-. ③ GS/TCH/RPI of 2.7°/41/874 avbl O/R.

MISSED APPROACH:

Rwy 13L: Climb on track 127° to 5000, then turn left direct YOD NDB or UOD R-330 at 15 DME.

Rwy 22: Climb on track 217° to 5000, then turn right direct YOD NDB or UOD R-235 at 15 DME.

Rwy 31R: Climb on track 307° to 5000, then turn right direct YOD NDB or UOD R-090 at 15 DME.

RADAR INSTRUMENT APPROACH MINIMUMS