

COMOX (CYQQ)

IFR TAKE-OFF MINIMUMS AND DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

CIVIL USERS: FAR 91 prescribes take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile.

Airports with IFR take-off minimums other than standard are listed below. Departure procedures and/or ceiling visibility minimums are established to assist all pilots conducting IFR flight in avoiding obstacles during climb to the minimum enroute altitude. Take-off minimums and departures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in feet MSL.

MILITARY USERS: Special IFR departure procedures not published as Standard Instrument Departure (SIDs) and civil take-off minima are included below and are established to assist pilots in obstacle avoidance. Refer to appropriate service directives for take-off minimums.

AIRPORT NAME	TAKE-OFF MINIMUMS
--------------	-------------------

COMOX (CYQQ) 06047

Comox, BC

Diverse departure not authorized.

Rwy 12 - TACAN (COMOX ONE)

Climb R-110 to 12 DME turn left to intercept R-080 proceed inbound to cross 6 DME at 7900 or assigned altitude (whichever is lower) climb on course. If unable, climb in holding until on R-080 between 6 and 12 DME until MEA, right turns.

Rwy 30 - TACAN (COMOX TWO),

Right turn climb R-330 to 12 DME, turn left to intercept R-300 and proceed inbound to cross 6 DME at 7900 or assigned altitude (whichever is lower) climb on course. If unable, climb in holding until on R-300 between 6 and 12 DME until MEA, left turns.

NOTE: CAT E aircraft climb in holding between 6 and 15 DME.

Rwy 12 - NDB (COMOX THREE)

Climb to 2200 on track of 112°, left turn direct QQNDB. Cross QQNDB at 7900 or assigned altitude (whichever is lower) climb on course. If unable, climb in holding on QQNDB inbound track 301° until MEA, right turns.

Rwy 30 - NDB (COMOX FOUR)

Climb direct to QQNDB turn right to 3000 on track of 302° left turn direct to QQNDB. Cross NDB at 7900 or assigned altitude (whichever is lower) climb on course. If unable, climb in holding on QQNDB inbound track 112°.

All departures cross DER at or above 35' AGL.