

## **BAGOTVILLE (CYBG)**

### **▼ IFR TAKE-OFF MINIMUMS AND DEPARTURE PROCEDURES**

#### **Civil Airports and Selected Military Airports**

CIVIL USERS: FAR 91 prescribes take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile.

Airports with IFR take-off minimums other than standard are listed below. Departure procedures and/or ceiling visibility minimums are established to assist all pilots conducting IFR flight in avoiding obstacles during climb to the minimum enroute altitude. Take-off minimums and departures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in feet MSL.

MILITARY USERS: Special IFR departure procedures not published as Standard Instrument Departure (SIDs) and civil take-off minima are included below and are established to assist pilots in obstacle avoidance. Refer to appropriate service directives for take-off minimums.

<b>AIRPORT NAME</b>	<b>TAKE-OFF MINIMUMS</b>
---------------------	--------------------------

#### **BAGOTVILLE (CYBG)**

Bagotville, QC

Rwy 11, minimum climb of 220/NM to 4400  
before proceeding on course.

Rwy 36, minimum climb of 210/NM to 4400  
before proceeding on course.

All departures cross DER at or above 35'  
AGL.