

GREENWOOD (CYZX)

✈ IFR TAKE-OFF MINIMUMS AND DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

CIVIL USERS: FAR 91 prescribes take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile.

Airports with IFR take-off minimums other than standard are listed below. Departure procedures and/or ceiling visibility minimums are established to assist all pilots conducting IFR flight in avoiding obstacles during climb to the minimum enroute altitude. Take-off minimums and departures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in feet MSL.

MILITARY USERS: Special IFR departure procedures not published as Standard Instrument Departure (SIDs) and civil take-off minima are included below and are established to assist pilots in obstacle avoidance. Refer to appropriate service directives for take-off minimums.

AIRPORT NAME	TAKE-OFF MINIMUMS
---------------------	--------------------------

GREENWOOD (CYZX)

Greenwood, NS

Rwy 08/26, climb rwy heading to 1200 before proceeding on course.

Rwy 12, climb rwy heading with minimum climb of 310/NM to 800 before proceeding on course.

Rwy 30, climb rwy heading with minimum climb of 290/NM to 1200 before proceeding on course.

All departures cross DER at or above 35' AGL.