

QUEBEC/JEAN LESAGE INTL (CYQB)

✈ IFR TAKE-OFF MINIMUMS AND DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

CIVIL USERS: FAR 91 prescribes take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile.

Airports with IFR take-off minimums other than standard are listed below. Departure procedures and/or ceiling visibility minimums are established to assist all pilots conducting IFR flight in avoiding obstacles during climb to the minimum enroute altitude. Take-off minimums and departures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in feet MSL.

MILITARY USERS: Special IFR departure procedures not published as Standard Instrument Departure (SIDs) and civil take-off minima are included below and are established to assist pilots in obstacle avoidance. Refer to appropriate service directives for take-off minimums.

AIRPORT NAME	TAKE-OFF MINIMUMS
--------------	-------------------

QUEBEC/JEAN LESAGE INTL (CYQB) 06047

Quebec, QC

Rwy 30, fly heading 295° until 660, then climbing left turn heading 274° until passing 2400. Requires minimum climb rate of 290 ft per mile until passing 1600.

Rwy 06, Climb to BV NDB then outbound track 064° to 2500 before proceeding on course.

Rwys 12, 24 Departure-Do not proceed in North sector between Rwys 06 and 30 before reaching 1600.

All departures cross DER at or above 35' AGL.