

BUSCO-EIGHT DEPARTURE

GLENDALE, ARIZONA


ATIS ★134.925 269.9
 CLNC DEL
 126.25 273.475
 GND CON
 133.175 335.8
 LUKE TOWER ★
 119.1 379.9
 LUKE DEP CON
 125.45 263.125

SH-321 [USAF]

Rwy	Knots	120	180	240	300	360
* 3R	V/V(fpm)	540	810	1080	1350	1620
* 3L	V/V(fpm)	520	780	1040	1300	1560

* Minimum Climb Rate

* From departure Rwy 3 to 4900'



ATC Climb Rate

Rwy	Knots	120	180	240	300	360
⊙ 3L	V/V(fpm)	560	840	1120	1400	1680
⊙ 3R	V/V(fpm)	540	810	1080	1350	1620
⊙ 21L	V/V(fpm)	660	990	1320	1650	1980
⊙ 21R	V/V(fpm)	680	1020	1360	1700	2040

⊙ From departure end to FATUX

⊙ From departure end to BUSCO

• 4512

RADAR REQUIRED

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 3L/R: Climb on a track of 030°. Abeam ZOBEG (LUF R-030/4 DME) turn left and track 212° to intercept GBN R-360 at FATUX (GBN R-360/38 DME) to BUSCO (GBN R-360/23 DME). Cross FATUX at and maintain 6000. Then via (assigned route/transition).

TAKE-OFF RWY 21L/R: Climb on a track of 211° to intercept GBN R-360 at HEBOS (GBN R-360/27 DME) to BUSCO (GBN R-360/23 DME). Cross abeam EZRUN (LUF R-211/8 DME) above 3000 and below 5000. Cross BUSCO at and maintain 6000. Then via (assigned route/transition).

FLIER TRANSITION (BUSCO8•FLIER): Turn left on a track of 150° to FETPI (GBN R-082/13.3). At FETPI turn left on a track of 137° to FLIER (GBN R-106/29). Cross GBN R-011 at 6000. Cross GBN R-062 at or below 8000. Cross FLIER at and maintain 9000 (or as assigned by ATC).

BUGGS TRANSITION

(BUSCO8•BUGGS(BU8BG)) / (BUSCO8•SELLS(BU8SL)) / (BUSCO8•AR647(BU8AR): Turn left on a track of 150° to BUGGS (GBN R-122/27 DME). Cross GBN R-011 at 6000. Cross GBN R-062 at or below 8000. Cross GBN R-092 at and maintain 9000 (or as assigned by ATC) to BUGGS (GBN R-122/27 DME). NOTE: CAUTION: AIRCRAFT EXITING BUGGS AT 8000.

BUSCO-EIGHT DEPARTURE

GLENDALE, ARIZONA

LUKE AFB (KLUF)

Effective 3 AUG 2006 - 31 AUG 2006